SAFETY DATA SHEET
(in accordance with Regulation (EU) 2020/878)

BPTM 6138-MOPCLEANER DESTELLO

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: MOPCLEANER DESTELLO
Product Code: BPTM 6138
UFI: EG40-706D-4006-72G4

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Traps dust and polishes floors, impregnating the mop.

Uses advised against: Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **QUIMI ROMAR S.L.**
Address: Ctra. Moncada a Náquera, CV-315, Km 11,2
City: 46119 - Náquera
Province: Valencia (ESPAÑA)
Telephone: (+34) 96 139 07 92
Fax: (+34) 96 139 00 36
E-mail: info@quimiromar.com
Web: www.quimiromar.com

1.4 Emergency telephone number: (+34) 96 139 07 92 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.
In accordance with Regulation (EC) No 1272/2008:
Aerosol 1 : Pressurised container: May burst if heated.
Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

2.2 Label elements.
Labelling in accordance with Regulation (EC) No 1272/2008:
Pictograms:

Signal Word:
Danger
Hazard statements:
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P262 Do not get in eyes, on skin or on clothing.

-Continued on next page.-

P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P501	Dispose of contents/container in an authorised consultant.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50ºC/122ºF.

Avoid extended spraying.
Do not ingest.

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.
Not Applicable.

3.2 Mixtures.
Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 603-002-00-5 CAS No: 64-17-5 EC No: 200-578-6 Registration No: 01-2119457610-43-XXXX	[2] ethanol, ethyl alcohol	>= 50% < 75 %	Flam. Liq. 2, H225	-
Index No: 649-083-00-0 CAS No: 68512-91-4 EC No: 270-990-9 Registration No: 01-2119485926-20-XXXX	GLP	>= 25% < 50 %	Flam. Gas 1, H220 Press. Gas, H280	-
CAS No: 64742-49-0 Registration No: 01-2119475515-33-XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	>= 5% < 10 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT SE 3, H336 - Skin Irrit. 2, H315	-
CAS No: 8042-47-5 EC No: 232-455-8 Registration No: 01-2119487078-27-XXXX	[2] White mineral oil (petroleum)	>= 2,5% < 5%	Asp. Tox. 1, H304	-
CAS No: 140-11-4 EC No: 205-399-7 Registration No: 01-2119638272-42-XXXX	[2] Benzyl acetate	<0,1%	Aquatic Chronic 3, H412	-

-Continued on next page.-

CAS No: 80-56-8 EC No: 201-291-9 Registration No: 01-2119519223-49-XXXX	alpha-Pinene	<0,1%	Acute Tox. 4, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 607-130-00-2 CAS No: 123-92-2 EC No: 204-662-3 Registration No: 01-2119548408-32-XXXX	[1] [2] isopentyl acetate	<0,1%	Flam. Liq. 3, H226	-
CAS No: 127-91-3 EC No: 204-872-5 Registration No: 01-2119519230-54-XXXX	Pin-2(10)-ene	<0,1%	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 601-096-00-2 CAS No: 5989-27-5 EC No: 227-813-5 Registration No: 01-2119529223-47-XXXX	R)-p-mentha-1,8-diene, d-limonene	<0,1%	Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 3, H412 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1B, H317	-

(*) *The complete text of the H phrases is given in section 16 of this Safety Data Sheet.*
[1] Substance with a European Union exposure limit in the workplace (see section 8.1).
[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.
In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.
Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.
Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.
Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.
If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.
No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

-Continued on next page.-

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

In case of fire, as a general hazard, heat can cause containers to explode.
The product is Extremely inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.
Suitable extinguishing media:
Extinguisher powder or CO2.

Unsuitable extinguishing media:
Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.
Special risks.
Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:
- Flammable vapors or gases.
- Explosions.

5.3 Advice for firefighters.
Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available. Move containers away from the area if there is no danger in doing so. Keep away from containers and continue cooling them from a safe place. Stop the leak if this can be done safely and do not put out fire until the leak has been closed off. If it is not possible to keep the fire under control, leave the area and let it burn.

Fire protection equipment.
According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.
Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. Isolate the area and ensure adequate ventilation. Stockpiling in basements, pits or any confined space or depressed area can be hazardous. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.
Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.
Use soapsuds to detect small leaks. Stop the leak if this can be done safely. Ensure adequate ventilation to prevent the accumulation of gases or vapours.

En caso de que el gas condense:
Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant. Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

-Continued on next page.-

6.4 Reference to other sections.
For exposure control and individual protection measures, see section 8.
For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.
The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.
The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.
Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.
In the application area, smoking, eating, and drinking must be prohibited.
Follow legislation on occupational health and safety.
Pressurised gases must be handled by suitably trained and experienced individuals. Use equipment suitable for supply pressure and temperature. Protect containers against physical damage and keep valves clean and in perfect condition. Do not tamper with original packaging.

7.2 Conditions for safe storage, including any incompatibilities.
Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 º C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. It must not be stored under conditions conducive to corrosion of the container. Protect containers against physical damage and inspect them regularly to ensure they are in good condition.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).
Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
ethanol, ethyl alcohol	64-17-5	United Kingdom [1]	**Eight hours**	1000	1920
			Short term		
		Éire [2]	**Eight hours**		
			Short term	1000	
		United States [3] (Cal/OSHA)	**Eight hours**	1000	
			Short term		
		United States [4] (NIOSH)	**Eight hours**	1000	
			Short term		
		United States [5] (OSHA)	**Eight hours**	1000	1900
			Short term		
White mineral oil (petroleum)	8042-47-5	Éire [2]	**Eight hours**		5
			Short term		
Benzyl acetate	140-11-4	Éire [2]	**Eight hours**	10	
			Short term		
isopentyl acetate	123-92-2		**Eight hours**	50	270

-Continued on next page.-

		European Union [6]	**Short term**	100	540
		Éire [2]	**Eight hours**	50	260
			Short term	100	520
		United States [3] (Cal/OSHA)	**Eight hours**	50	
			Short term	100	
		United States [4] (NIOSH)	**Eight hours**	100	
			Short term		
		United States [5] (OSHA)	**Eight hours**	100	525
			Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.
[2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).
[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
[4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.
[5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
[6] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).
The product does NOT contain substances with Biological Limit Values.
Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	DNEL (Workers)	Inhalation, Chronic, Systemic effects	950 (mg/m³)
Benzyl acetate CAS No: 140-11-4 EC No: 205-399-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	21,9 (mg/m³)
alpha-Pinene CAS No: 80-56-8 EC No: 201-291-9	DNEL (Workers)	Inhalation, Chronic, Systemic effects	5,98 (mg/m³)
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	DNEL (Workers)	Inhalation, Chronic, Systemic effects	20,8 (mg/m³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	5,1 (mg/m³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	2,95 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	1,47 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	1,47 (mg/kg bw/day)
Pin-2(10)-ene CAS No: 127-91-3 EC No: 204-872-5	DNEL (Workers)	Inhalation, Chronic, Systemic effects	5,98 (mg/m³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
Concentration levels PNEC:

Name	Details	Value
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	Fresh water	0,96 (mg/L)
	Marine water	0,79 (mg/L)
	aqua (intermittent releases)	2,75 (mg/L)
	Soil	0,63 (mg/kg soil dw)

-Continued on next page.-

	sediment (freshwater)	3,6 (mg/kg sediment dw)
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	aqua (freshwater)	0,022 (mg/L)
	aqua (marine water)	0,0022 (mg/L)
	aqua (intermittent releases)	0,22 (mg/L)
	STP	30 (mg/L)
	sediment (freshwater)	17,87 (mg/kg sediment dw)
	sediment (marine water)	1,787 (mg/kg sediment dw)
	soil	4,15 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:
Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	**100 %**		
Uses:	**Traps dust and polishes floors, impregnating the mop.**		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Work gloves.		
Characteristics:	«CE» marking, category I.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
Eye protection:			
PPE:	Face shield.		
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.		
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.		
Skin protection:			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		

-Continued on next page.-

Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Anti-static safety footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance:	The footwear should be checked regularly
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.
Physical state: Gas - liquefied
Colour: Colourless
Odour: Characteristic of perfume
Odour threshold: Not applicable/Not available due to the nature/properties of the product
Melting point: Not applicable/Not available due to the nature/properties of the product
Freezing point: Not applicable/Not available due to the nature/properties of the product
Boiling point or initial boiling point and boiling range: >35 ºC
Flammability: Not applicable/Not available due to the nature/properties of the product
Lower explosion limit: Not applicable/Not available due to the nature/properties of the product
Upper explosion limit: Not applicable/Not available due to the nature/properties of the product
Flash point: <23 ºC
Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product
pH: Not applicable (Substance/mixture is a gas).
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product
Solubility: Not applicable/Not available due to the nature/properties of the product
Hydrosolubility: Not applicable/Not available due to the nature/properties of the product
Liposolubility: Not applicable/Not available due to the nature/properties of the product
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product
Vapour pressure: Not applicable/Not available due to the nature/properties of the product
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: Not applicable/Not available due to the nature/properties of the product
Relative vapour density: Not applicable/Not available due to the nature/properties of the product
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information
Viscosity: Not applicable/Not available due to the nature/properties of the product
Explosive properties: Not applicable/Not available due to the nature/properties of the product
Oxidizing properties: Not applicable/Not available due to the nature/properties of the product
Dropping point: Not applicable/Not available due to the nature/properties of the product
Blink: Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.
If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.
Unstable in contact with:
- Acids.
- Bases.
- Oxidizing agents.

-Continued on next page.-

10.3 Possibility of hazardous reactions.
Extremely flammable aerosol.
Pressurised container: May burst if heated.
In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.
Avoid the following conditions:
- Heating.
- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials.
Avoid the following materials:
- Acids.
- Bases.
- Oxidizing agents.
- Explosives materials.
- Toxic materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.
Depending on conditions of use, can be generated the following products:
- COx (carbon oxides).
- Organic compounds.
In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	**Test**	**Kind**	**Value**
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	Oral	LD50	Rabbit	7410 mg/kg bw [1] [1] Aliphatic alcohols and alkyl esters. Narcotic and lethal potencies to tadpoles and to rabbits. Munch, J.C. 1972.
	Dermal	LD50	Rabbit	>5000 mg/kg [1] [1] review: OPDYKE D L J, FOOD COSMET TOXICOL, 13 (5), 545-554, 1975. original source mentioned: Moreno, O.M. (1973). Report to RIFM, 1 February. Opdyke D L J 1975.
	Inhalation	LOAEL	Cat	11600 mg/m³ air [1] [1] Ferdinand Flury und Wolfgang Wirth, International Archives of Occupational and Environmental Health Springer Berlin / Heidelberg ISSN 0340-0131 (Print), Heft Volume 5, Number 1, Seiten 1-90, Dezember 1933, DOI 10.1007/BF02274996

a) acute toxicity;
Not conclusive data for classification.

b) skin corrosion/irritation;
Based on available data, the classification criteria are not met.

-Continued on next page.-

c) serious eye damage/irritation;
Not conclusive data for classification.

d) respiratory or skin sensitisation;
Based on available data, the classification criteria are not met.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Based on available data, the classification criteria are not met.

11.2 Information on other hazards.
Endocrine disrupting properties
This product does not contain components with endocrine-disrupting properties with effects on human health.
Other information
There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	Fish	LC50	Leuciscus idus melanotus	36 mg/l (48 h) [1] [1] Fish toxicity (mg/l) Lüdemann WaBoLu Berlin. The methodology was based on the static fish test with the Gold orfe (Leuciscus idus melanotus), according to Mann (1975, 1976), published in Vom Wasser 46 (1976).
	Aquatic invertebrates	EC50	Daphnia magna Straus	205 mg/l (24 h) [1] [1] Experimental result, Prüfvorschrift DIN 38412 Teil 11.
	Aquatic plants	ErC50	Desmodesmus subspicatus	>100 mg/l (48 h) [1] [1] Study report, 2010. OECD Guideline 201 (Alga, Growth Inhibition Test).

12.2 Persistence and degradability.
No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.
No information is available about persistence and degradability of the product.

-Continued on next page.-

The surfactants contained in this product fulfill the biodegradability criteria stipulated in Regulation (EC) No. 648/2004 on detergents.
The data that justifies this affirmation is available to the competent authorities that request it.

12.3 Bioaccumulative potential.
Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	-0,3	-	-	Very low
White mineral oil (petroleum) CAS No: 8042-47-5 EC No: 232-455-8	0	-	-	Very low
Benzyl acetate CAS No: 140-11-4 EC No: 205-399-7	1,96	-	-	Very low
alpha-Pinene CAS No: 80-56-8 EC No: 201-291-9	4,48	-	-	High
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	2,26	-	21,5 mg/L	Low
Pin-2(10)-ene CAS No: 127-91-3 EC No: 204-872-5	4,16	-	-	High

12.4 Mobility in soil.
No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.
No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.
This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.
No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.
Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

-Continued on next page.-

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.
Land: Transport by road: ADR, Transport by rail: RID.
Transport documentation: Consignment note and written instructions
Sea: Transport by ship: IMDG.
Transport documentation: Bill of lading
Air: Transport by plane: ICAO/IATA.
Transport document: Airway bill.

14.1 UN number or ID number.
UN No: UN1950

14.2 UN proper shipping name.
Description:
ADR/RID: UN 1950, AEROSOLS, 2.1, (D)
IMDG: UN 1950, AEROSOLS, 2.1 (23ºC)
ICAO/IATA: UN 1950, AEROSOLS, 2.1

14.3 Transport hazard class(es).
Class(es): 2

14.4 Packing group.
Packing group: Not applicable.

14.5 Environmental hazards.
Marine pollutant: No
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-D,S-U

14.6 Special precautions for user.

ADR LQ: 1 L
IMDG LQ: 120 ml
ICAO LQ: Not applicable.



Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.
The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.
The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)
VOC content (p/p): 96,676 %
VOC content: 770,774 g/l

Contains in accordance with Regulation (EC) No 648/2004 on detergents:

aliphatic hydrocarbons	> 30%
perfumes	

-Continued on next page.-

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A
The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.
The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.
No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aerosol 1 : Flammable aerosol, Category 1
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Asp. Tox. 1 : Aspiration toxicity, Category 1
Flam. Gas 1 : Flammable gas, Category 1
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Press. Gas : Gases under pressure
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1B : Skin sensitiser, Category 1B

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

-Continued on next page.-

Abbreviations and acronyms used:
ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AwSV: Facility Regulations for handling substances that are hazardous for the water.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK: Water hazard classes.

Key literature references and sources for data:
http://eur-lex.europa.eu/homepage.html
http://echa.europa.eu/
Regulation (EU) 2020/878.
Regulation (EC) No 1907/2006.
Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

-End of safety data sheet.-