

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 1 of 12
Print date: 30/01/2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY
Product Code: BPTM 6193
UFI: 18R4-X01J-G005-8SJE

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Renewed & Polisher for all car interior surfaces. Cleans & Preserves plastic, vinyl, leatherette, leather, etc.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **QUIMI ROMAR S.L.**
Address: Ctra. Moncada a Náquera, CV-315, Km 11,2
City: 46119 - Náquera
Province: Valencia (ESPAÑA)
Telephone: (+34) 96 139 07 92
Fax: (+34) 96 139 00 36
E-mail: info@quimiromar.com
Web: www.quimiromar.com

1.4 Emergency telephone number: (+34) 96 139 07 92 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Asp. Tox. 1 : May be fatal if swallowed and enters airways.

STOT SE 3 : May cause drowsiness or dizziness.

Skin Irrit. 2 : Causes skin irritation.

Aerosol 1 : Pressurised container: May burst if heated.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Danger

Hazard statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 2 of 12
Print date: 30/01/2023

Precautionary statements:

- P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P262 Do not get in eyes, on skin or on clothing.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P501 Dispose of contents/container in an authorised consultant.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P301+P312 Call a POISON CENTER or a doctor if you feel unwell.
Do not ingest.
Avoid extended spraying.
Do not ingest.

Contains: Naphtha (petroleum), hydrotreated light

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index N°: 649-083-00-0 CAS N°: 68512-91-4 EC N°: 270-990-9 Registration N°: 01-2119485926-20-XXXX	GLP	>= 50% < 75%	Flam. Gas 1, H220 Press. Gas, H280	-
CAS No: 64742-49-0 Registration No: 01-2119475515-33-XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	>=10% < 25%	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT SE 3, H336 - Skin Irrit. 2, H315	-
Index No: 603-002-00-5 CAS No: 64-17-5 EC No: 200-578-6 Registration No: 01-2119457610-43-XXXX	[2] ethanol, ethyl alcohol	>=10% < 25%	Flam. Liq. 2, H225	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 3 of 12
Print date: 30/01/2023

CAS No: 140-11-4 EC No: 205-399-7 Registration No: 01-2119638272-42-XXXX	[2] Benzyl acetate	<0,1%	Aquatic Chronic 3, H412	-
--	--------------------	-------	-------------------------	---

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

SECTION 5: FIREFIGHTING MEASURES.

In case of fire, as a general hazard, heat can cause containers to explode.

The product is Extremely inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 4 of 12
Print date: 30/01/2023

- Explosions.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available. Move containers away from the area if there is no danger in doing so. Keep away from containers and continue cooling them from a safe place. Stop the leak if this can be done safely and do not put out fire until the leak has been closed off. If it is not possible to keep the fire under control, leave the area and let it burn.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. Isolate the area and ensure adequate ventilation. Stockpiling in basements, pits or any confined space or depressed area can be hazardous. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Use soapsuds to detect small leaks. Stop the leak if this can be done safely. Ensure adequate ventilation to prevent the accumulation of gases or vapours.

En caso de que el gas condense:

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant. Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Pressurised gases must be handled by suitably trained and experienced individuals. Use equipment suitable for supply pressure and temperature. Protect containers against physical damage and keep valves clean and in perfect condition. Do not tamper with original packaging.

7.2 Conditions for safe storage, including any incompatibilities.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 5 of 12
Print date: 30/01/2023

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. It must not be stored under conditions conducive to corrosion of the container. Protect containers against physical damage and inspect them regularly to ensure they are in good condition.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
ethanol, ethyl alcohol	64-17-5	United Kingdom [1]	Eight hours	1000	1920
			Short term		
		Éire [2]	Eight hours		
			Short term	1000	
		United States [3] (Cal/OSHA)	Eight hours	1000	
			Short term		
United States [4] (NIOSH)	Eight hours	1000			
	Short term				
United States [5] (OSHA)	Eight hours	1000	1900		
	Short term				
Benzyl acetate	140-11-4	Éire [2]	Eight hours	10	
			Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	DNEL (Workers)	Inhalation, Chronic, Systemic effects	950 (mg/m ³)
Benzyl acetate CAS No: 140-11-4 EC No: 205-399-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	21,9 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	Fresh water	0,96 (mg/L)
	Marine water	0,79 (mg/L)
	aqua (intermittent releases)	2,75 (mg/L)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 6 of 12
Print date: 30/01/2023

	Soil	0,63 (mg/kg soil dw)
	sediment (freshwater)	3,6 (mg/kg sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %				
Uses:	Renewed & Polisher for all car interior surfaces. Cleans & Preserves plastic, vinyl, leatherette, leather, etc.				
Breathing protection:					
PPE:	Filter mask for protection against gases and particles.				
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.				
CEN standards:	EN 136, EN 140, EN 405				
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.				
Observations:	P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.				
Filter Type needed:	A2				
Hand protection:					
PPE:	Protective gloves against chemicals.				
Characteristics:	«CE» marking, category III.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:					
PPE:	Protective goggles with built-in frame.				
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.				
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.				
Skin protection:					
PPE:	Anti-static protective clothing.				
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.				
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.				
PPE:	Anti-static safety footwear.				
Characteristics:	«CE» marking, category II.				

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 7 of 12
Print date: 30/01/2023

CEN standards: EN ISO 13287, EN ISO 20344, EN ISO 20346



Maintenance: The footwear should be checked regularly
The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

Observations:

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Gas - liquefied

Colour: Colourless

Odour: Characteristic perfume

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: >35 °C

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: <23 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable (Substance/mixture is a gas).

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 0,760

Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Extremely flammable aerosol.

Pressurised container: May burst if heated.

10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 8 of 12
Print date: 30/01/2023

10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Product classified:

Aspiration toxicity, Category 1: May be fatal if swallowed and enters airways.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 9 of 12
Print date: 30/01/2023

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	-0,3	-	-	Very low
Benzyl acetate CAS No: 140-11-4 EC No: 205-399-7	1,96	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 10 of 12
Print date: 30/01/2023

Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1950

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1950, AEROSOLS, 2.1, (D)

IMDG: UN 1950, AEROSOLS, 2.1 (23°C)

ICAO/IATA: UN 1950, AEROSOLS, 2.1

14.3 Transport hazard class(es).

Class(es): 2

14.4 Packing group.

Packing group: Not applicable.

14.5 Environmental hazards.

Marine pollutant: No


Transport by ship, FEM – Emergency sheets (F – Fire, S - Spills): F-D,S-U

14.6 Special precautions for user.

ADR LQ: 1 L

IMDG LQ: 120 ml

ICAO LQ: Not applicable.



Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 99,639 %

VOC content: 757,26 g/l

Contains in accordance with Regulation (EC) No 648/2004 on detergents:

aliphatic hydrocarbons

> 30%

perfumes

Allergens: BENZYL SALICYLATE

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 11 of 12
Print date: 30/01/2023

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Aerosol 1 : Flammable aerosol, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Asp. Tox. 1 : Aspiration toxicity, Category 1
Flam. Gas 1 : Flammable gas, Category 1
Flam. Liq. 2 : Flammable liquid, Category 2
Press. Gas : Gases under pressure
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Irrit. 2 : Skin irritant, Category 2

Changes regarding to the previous version:

- Change of the name of the product (SECTION 1.1).
- Changes in the information of the supplier (SECTION 1.3).
- Modification of specific hazards (SECTION 2.3).
- Modification in the firefighting measures (SECTION 5.1).
- Modification in the firefighting measures (SECTION 5.2).
- Modification in the firefighting measures (SECTION 5.3).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

BPTM 6193-DASHBOARD VINYL AND PLASTIC CLEANER TROPICAL COCONUT FRAGRANCE GARLEY



Version 2 (replaces version 1)

Revision date: 30/01/2023

Page 12 of 12
Print date: 30/01/2023

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AwSV: Facility Regulations for handling substances that are hazardous for the water.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.